

Sustainment Systems  
**Power Solutions**



DRS Pivotal Power continues to invest in advanced equipment. Our facilities and services include in-house test chambers for environmental screening, Electromagnetic Interference/ Electromagnetic Compatibility (EMI/EMC) confidence testing, vibration testing and full functional testing from 100 W to 100 kW. Through this unique combination of experience and design production testing capability, we are able to deliver the right power equipment for you.

DRS Pivotal Power's 2 KVA AC Uninterruptible Power Supply (UPS) produces precise 115 VAC 60 Hz output power to comply with the stringent system requirements of STANAG 1008 specification for critical naval shipboard applications. In the event of loss of input power, the UPS is capable of supplying the rated output power for 15 minutes minimum, using internal batteries, with no transient interruptions.

The power conversion of the UPS is based on switch mode technology using high-frequency Pulsewidth Modulation (PWM), which provides sinusoidal output voltage with very low distortion even under adverse non-linear loading conditions. The use of power Metal-Oxide-Semiconductor Field-Effect Transistors (MOSFETs) as switching elements ensures high conversion efficiency.

The construction of the UPS is modular with draw-out type subassemblies for ease of maintenance. The system reliability is an order of magnitude greater than other static conversion equipment due to the use of high reliability components and stringent quality screening standards.

The UPS was developed and fully qualified for military applications

DRS PIVOTAL POWER



## Features

- Isolation switches for input, output and battery
- Draw-out subassemblies and printed wiring boards
- Built-In-Test (BIT) capability
- Online maintenance of batteries and battery charger
- Output voltmeter
- LED status indication for input, output, backup mode operation, low battery, over current, over temperature and unit shutdown
- Fault signal for remote indication
- Circular coupling connectors for input and output
- Secondary fuse protection for output

## Input

Voltage . . . . . 440 VAC nominal, 3 phase  
Frequency . . . . . 60 Hz nominal

## Output

Applicable standard . . . . . STANAG 1008  
Voltage . . . . . 115 VAC, single phase  
Frequency . . . . . 60 Hz  
Rating . . . . . 2 kVA  
Power backup time . . . . . 15 minutes minimum at rated load  
Efficiency . . . . . 82% at rated load

## Environmental

Operating temperature . . . . . -30°C to 45°C / -22°F to 113°F  
Humidity . . . . . up to 95% RH non-condensing  
EMI/EMC . . . . . MIL-STD-461C, Part 5, surface ships  
Vibration . . . . . MIL-STD-167-1, Type 1, 5 Hz to 25 Hz  
Shock resistance . . . . . MIL-S-901C, Type A, Grade A Class 1  
Airborne noise . . . . . MIL-STD-740B, Class B  
Cooling method . . . . . forced air convection

## Physical

Dimensions . . . . . 25.5 L x 19.0 W x 40.0 H inches  
648 L x 483 W x 1,016 H mm  
Weight (including batteries) . . . . . 440 lbs. (max)  
200 kg (max)

Specifications subject to change without notice.

DRS PIVOTAL POWER  
150 Bluewater Road  
Bedford, Nova Scotia, Canada B4B 1G9

902.835.7268  
Fax 902.835.6026  
defence@pivotalpower.com  
www.drs.com