

Sustainment Systems
Power Solutions



DRS Pivotal Power continues to invest in advanced equipment. Our facilities and services include in-house test chambers for environmental screening, Electromagnetic Interference/ Electromagnetic Compatibility (EMI/EMC) confidence testing, vibration testing and full functional testing from 100 W to 100 kW. Through this unique combination of experience and design production testing capability, we are able to deliver the right power equipment for you.

DRS Pivotal Power's 2 KVA AC Uninterruptible Power Supply (UPS) produces precise 115 VAC 60 Hz output power to comply with the stringent system requirements of STANAG 1008 specification for critical naval shipboard applications. In the event of loss of input power, the UPS is capable of supplying the rated output power for 15 minutes minimum, using internal batteries, with no transient interruptions.

The power conversion of the UPS is based on switch mode technology using high-frequency Pulsewidth Modulation (PWM), which provides sinusoidal output voltage with very low distortion even under adverse non-linear loading conditions. The use of power Metal-Oxide-Semiconductor Field-Effect Transistors (MOSFETs) as switching elements ensures high conversion efficiency.

The construction of the UPS is modular with draw-out type subassemblies for ease of maintenance. The system reliability is an order of magnitude greater than other static conversion equipment due to the use of high reliability components and stringent quality screening standards.

The UPS was developed and fully qualified for military applications

DRS PIVOTAL POWER



Features

- Isolation switches for input, output and battery
- Draw-out subassemblies and printed wiring boards
- Built-In-Test (BIT) capability
- Online maintenance of batteries and battery charger
- Output voltmeter
- LED status indication for input, output, backup mode operation, low battery, over current, over temperature and unit shutdown
- Fault signal for remote indication
- Circular coupling connectors for input and output
- Secondary fuse protection for output

Input

Voltage 440 VAC nominal, 3 phase
Frequency 60 Hz nominal

Output

Applicable standard STANAG 1008
Voltage 115 VAC, single phase
Frequency 60 Hz
Rating 2 kVA
Power backup time 15 minutes minimum at rated load
Efficiency 82% at rated load

Environmental

Operating temperature -30°C to 45°C / -22°F to 113°F
Humidity up to 95% RH non-condensing
EMI/EMC MIL-STD-461C, Part 5, surface ships
Vibration MIL-STD-167-1, Type 1, 5 Hz to 25 Hz
Shock resistance MIL-S-901C, Type A, Grade A Class 1
Airborne noise MIL-STD-740B, Class B
Cooling method forced air convection

Physical

Dimensions 25.5 L x 19.0 W x 40.0 H inches
648 L x 483 W x 1,016 H mm
Weight (including batteries) 440 lbs. (max)
200 kg (max)

Specifications subject to change without notice.

DRS PIVOTAL POWER
150 Bluewater Road
Bedford, Nova Scotia, Canada B4B 1G9

902.835.7268
Fax 902.835.6026
defence@pivotalpower.com
www.drs.com

11/06

DRS PIVOTAL POWER

